

## Datasheet

# Prelude T-24 CR



Prelude T-24 CR is an exposed 24 mm T-grid system. Special paint finish and TLX steel-based composite clip for enhanced corrosion resistance. Corrosion resistance 700 hours salt spray test on grids according to EN ISO 9227 standards. Durability Class C (EN13964:2014).

## Dimensions

Component	Width x Length	Height	Colour
Universal Main runner Corrosive Resistant Peakform	24 x 3600 mm	43 mm	White
Cross tee Corrosive Resistant TLX	24 x 1200 mm	38 mm	White
Cross tee Corrosive Resistant TLX	24 x 600 mm	30 mm	White
Perimeter trim Corrosive Resistant	19 x 3050 mm	24 mm	White

# Performances

## Reaction to Fire



A1

According to: EN 13964: 2014

The grid is able to cope with expansion due to heat in a fire and remain flat and stable so that no large gaps and cracks appear between grid and tile.

## Durability



Corrosion class C

According to: EN 13964: 2014

## Load Bearing



According to: EN 13964: 2014

# General info

### Packaging

Carton

### Facings

Baked polyester paint. Additional paint finish to the reverse of the grid, giving an extra layer of protection to the galvanised steel.

### Colours

Global white, nearest RAL 9003/NCS 0502-B

### Maintenance

Clean with mild household cleaner and soft cloth.  
Before cleaning the grid remove the ceiling tiles to prevent cleaning solution or dirt from getting on the tiles.

### Usage Conditions

Suspended ceiling substructure components for indoor use.  
May be used continuously in 100 % relative humidity at a temperature of 30 °C.

Parafon® is a registered trademark  
of the ROCKWOOL Group.



[www.parafon.com/linkedin](http://www.parafon.com/linkedin)



[www.parafon.com/youtube](http://www.parafon.com/youtube)

[www.parafon.com](http://www.parafon.com)

09/2020 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Parafon accepts no responsibility for printing errors.

**Parafon / Rockwool AB**  
Diabasvagen 9  
541 52 Skovde  
Sweden



E-mail: [order@parafon.com](mailto:order@parafon.com)  
Tel.: +46 500 101 100